

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name CARBON DIOXIDE, COMPRESSED

Synonyms CARBON DIOXIDE • CO2 • PRODUCT CODES: A2000 • R744 (CO2 REFRIGERANT)

1.2 Uses and uses advised against

Uses INDUSTRIAL APPLICATIONS ● SHIELDING GAS

1.3 Details of the supplier of the product

Supplier name Industrial Gases New Zealand Ltd t/a Eziswap Gas

Address 6 and 10 Canaveral Drive, Rosedale, Auckland, NEW ZEALAND

Telephone +64 9 444 0357 **Fax** +64 9 444 3509

Emailsales@eziswapgas.co.nzWebsitehttp://www.eziswapgas.co.nz

1.4 Emergency telephone numbers

Emergency 111 (NZ only)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO HAZARDOUS SUBSTANCES [CLASSIFICATION] REGULATIONS 2001

HSNO classifications

Compressed gases Contains gas under pressure; may explode if heated.

2.2 GHS Label elements

Signal word WARNING

Pictograms

 \Diamond

Hazard statements

H280 Contains gas under pressure; may explode if heated.

Prevention statements

P103 Read label before use.

Response statements

None allocated.

Storage statements

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statements

None allocated.

Page 1 of 6 SDS Date: 23 July 2020 Revision No: 1.0

CARBON DIOXIDE, COMPRESSED PRODUCT NAME

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
CARBON DIOXIDE	124-38-9	204-696-9	99.8%
OXYGEN	7782-44-7	231-956-9	<0.01%
WATER	7732-18-5	231-791-2	<0.008%

4. FIRST AID MEASURES

4.1 Description of first aid measures

None required. Eye

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available.

Skin

Ingestion is not considered a potential route of exposure. If dry ice powder is swallowed, drink large volumes Ingestion

of water and seek immediate medical attention.

None allocated. First aid facilities

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO2 cause increased respiration and headache.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.

5.4 Hazchem code

2T

2 Fine Water Spray.

Т Wear full fire kit and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

> SDS Date: 23 July 2020 Page 2 of 6

Revision No: 1.0

CARBON DIOXIDE, COMPRESSED PRODUCT NAME

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient		ppm	mg/m³	ppm	mg/m³
Carbon dioxide	WES (NZ)	5000	9000	30000	54000

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face Wear safety glasses. Wear leather gloves. Hands Wear safety boots. **Body**

Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator. Respiratory







9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

COLOURLESS GAS Appearance Odour **ODOURLESS Flammability** NON FLAMMABLE Flash point **NOT RELEVANT Boiling point NOT AVAILABLE Melting point NOT AVAILABLE NOT APPLICABLE Evaporation rate NOT APPLICABLE** pН Vapour density NOT AVAILABLE **NOT APPLICABLE** Specific gravity Solubility (water) 0.759 cm³/cm³ 6000 kPa @ 25°C Vapour pressure **Upper explosion limit** NOT RELEVANT

> SDS Date: 23 July 2020 Page 3 of 6

Revision No: 1.0

PRODUCT NAME CARBON DIOXIDE, COMPRESSED

9.1 Information on basic physical and chemical properties

Lower explosion limit **NOT RELEVANT** Partition coefficient **NOT AVAILABLE Autoignition temperature NOT AVAILABLE** NOT AVAILABLE **Decomposition temperature NOT AVAILABLE** Viscosity **NOT AVAILABLE Explosive properties NOT AVAILABLE Oxidisiing properties Odour threshold NOT AVAILABLE**

9.2 Other information

% Volatiles 100 %

Density 1.84 g/L @ 20°C

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid contact with incompatible substances.

10.5 Incompatible materials

Moist carbon dioxide is corrosive, hence acid resistant materials are required (e.g. stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide (i.e. embrittlement, leaching of plasticisers, etc). The manufacturer reports that dusts of aluminium, chrome and manganese may ignite and explode when heated in carbon dioxide. Also incompatible with acrylaldehyde, aziridine, metal acetylide and sodium peroxide.

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Low concentrations of carbon dioxide cause

increased respiration and headache.

Skin Not classified as a skin irritant.

Eye Not classified as an eye irritant.

Sensitisation Not classified as causing skin or respiratory sensitisation.

MutagenicityNot classified as a mutagen.CarcinogenicityNot classified as a carcinogen.ReproductiveNot classified as a reproductive toxin.

STOT - single Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness,

exposure drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

Page 4 of 6 SDS Date: 23 July 2020 Revision No: 1.0

PRODUCT NAME CARBON DIOXIDE, COMPRESSED

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005; NZS 5433:2012, UN, IMDG OR IATA



	LAND TRANSPORT (NZS 5433)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)	
14.1 UN Number	1013	1013	1013	
14.2 Proper Shipping Name	CARBON DIOXIDE	CARBON DIOXIDE	CARBON DIOXIDE	
14.3 Transport hazard class	2.2	2.2	2.2	
14.4 Packing Group	None allocated.	None allocated.	None allocated.	

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code 2T EMS F-C, S-V

Other information Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Approval code HSR001018
Group standard Carbon dioxide

Inventory listings NEW ZEALAND: NZIOC (New Zealand Inventory of Chemicals)

All components are listed on the NZIoC inventory or are exempt.

16. OTHER INFORMATION

Additional information Some applications for compressed carbon dioxide include shielding arc welding, sparging, foundry

Page 5 of 6

sand mould curing and firefighting (fire extinguishers).

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

SDS Date: 23 July 2020 Revision No: 1.0

PRODUCT NAME CARBON DIOXIDE, COMPRESSED

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CCID Chemical Classification and Information Database (HSNO)

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

EPA Environmental Protection Authority [New Zealand]

GHS Globally Harmonized System

HSNO Hazardous Substances and New Organisms
IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value TWA Time Weighted Average

Prepared by

Industrial Gases New Zealand Ltd t/a Eziswap Gas

6 and 10 Canaveral Drive, Rosedale, Auckland, NEW ZEALAND

+64 9 444 0357

+64 9 444 3509

sales@eziswapgas.co.nz

http://www.eziswapgas.co.nz

[End of SDS]

SDS Date: 23 July 2020 Revision No: 1.0

Page 6 of 6