

# SAFETY DATA SHEET

## **1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

### 1.1 Product Identifier

**Product Name:** CARBON DIOXIDE, COMPRESSED **Synonyms:** CO<sub>2</sub>, Industrial Grade Carbon Dioxide **Product Code:** A2000

### 1.2 Relevant Identified Uses and Uses Advised Against

Identified Uses: Industrial applications, inerting, welding, water treatment Uses Advised Against: Not for medical or food use

### 1.3 Supplier Details

Supplier: Industrial Gases New Zealand Ltd t/a Eziswap Gas Address: 6 and 10 Canaveral Drive, Rosedale, Auckland, NEW ZEALAND Phone: +64 9 444 0357 Email: sales@eziswapgas.co.nz Website: http://www.eziswapgas.co.nz

### 1.4 Emergency Telephone Number

Emergency Telephone (NZ Only): 111

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the Substance or Mixture

- Gases under pressure Compressed gas
- Simple asphyxiant (may displace oxygen at high concentrations)

#### 2.2 GHS Label Elements

Signal Word: Pictogram: WARNING



#### Hazard Statements:

· H280: Contains gas under pressure; may explode if heated

#### **Precautionary Statements:**

- P103: Read label before use
- P410+P403: Protect from sunlight. Store in a well-ventilated place

### 2.3 Other Hazards

- · At high concentrations, may displace oxygen and cause asphyxiation
- · Rapid release of gas may cause cold burns or frostbite

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	CAS Number	EC Number	Content (v/v)	
Carbon Dioxide	124-38-9	204-696-9	>99.5%	

### 4. FIRST AID MEASURES

### **4.1 Description of First Aid Measures**

- · Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. Seek medical attention
- Skin Contact: In case of cold burn or frostbite, rinse with lukewarm water. Do not rub. Seek medical attention.
- Eye Contact: Rinse with water for several minutes. Remove contact lenses if present and easy to do. Seek medical advice.
- Ingestion: Not applicable.

### 4.2 Most Important Symptoms and Effects

- Dizziness, nausea, unconsciousness due to oxygen deficiency
- · Cold burns with exposure to liquefied gas

### 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- · Provide oxygen or ventilation support as required
- Treat symptomatically

## **5. FIRE FIGHTING MEASURES**

### 5.1 Extinguishing Media

Non-flammable gas. Use extinguishing agents appropriate for surrounding fire.

### 5.2 Special Hazards Arising from the Substance

- · Cylinders may rupture violently in fire conditions
- · May displace oxygen in confined areas

### 5.3 Advice for Firefighters

- · Use SCBA and full protective gear
- · Cool cylinders with water spray from a safe distance
- Evacuate area if leak or fire involves compressed gas

#### 5.4 Hazchem Code

2T

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- Evacuate area
- Ensure proper ventilation
- Avoid breathing gas
- Use SCBA in confined or low-oxygen environments

### **6.2 Environmental Precautions**

Avoid discharge into enclosed or poorly ventilated areas

### 6.3 Methods and Materials for Containment and Clean-Up

- Stop leak if safe to do so
- Vent gas to a safe, open area

### 6.4 Reference to Other Sections

See Sections 8 and 13

### 7. HANDLING AND STORAGE

### 7.1 Precautions for Safe Handling

- Use only with adequate ventilation
- Avoid contact with skin or eyes when handling cold gas
- Do not drop or handle cylinders roughly

### 7.2 Conditions for Safe Storage, Including Any Incompatibilities

- Store below 45°C in a secure, upright position
- · Keep away from heat, flames, or direct sunlight
- · Store in a well-ventilated area

### 7.3 Specific End Use(s)

Used in industrial and welding applications

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control Parameters (Workplace Exposure Standards - NZ WES 2022)

- Carbon Dioxide:
  - TWA: 2,500 ppm (4,900 mg/m<sup>3</sup>)
  - STEL: 4,870 ppm (9,400 mg/m<sup>3</sup>)

### 8.2 Exposure Controls

- Engineering Controls: Provide adequate general and local ventilation
- Personal Protective Equipment (PPE):
  - Eye Protection: Safety goggles
  - Skin Protection: Insulated gloves for cryogenic handling
  - Respiratory Protection: Use SCBA if oxygen levels are unknown or low



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value		
Appearance	Colourless, odourless gas		
Boiling Point	-78.5°C		
Vapour Pressure	~5,700 kPa at 20°C		
Vapour Density (Air=1)	1.52		
Solubility in Water	1.45 vol/vol		
рН	Slightly acidic in solution		
Flammability	Non-flammable		
Critical Temperature	31°C		

### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

Stable under recommended conditions

#### 10.2 Chemical Stability

Stable under normal temperature and pressure

### 10.3 Possibility of Hazardous Reactions

None expected under normal use

### 10.4 Conditions to Avoid

Heat, direct sunlight, and poor ventilation

#### **10.5 Incompatible Materials**

Alkali metals, strong bases, and oxidisers

#### 10.6 Hazardous Decomposition Products

Carbon monoxide (in case of incomplete combustion)

### **11. TOXICOLOGICAL INFORMATION**

- Acute Toxicity: Not classified
- Inhalation: Can displace oxygen and cause suffocation
- Skin/Eye Contact: May cause cold burns on contact with liquefied gas
- Chronic Effects: No long-term health effects expected at normal exposure levels

## **12. ECOLOGICAL INFORMATION**

- Ecotoxicity: Not harmful to aquatic or terrestrial life
- Persistence and Degradability: Readily disperses in air
- Bioaccumulation: Not applicable
- Mobility: High
- Other Adverse Effects: None known

## 13. DISPOSAL CONSIDERATIONS

- Product: Vent slowly to a safe, well-ventilated area
- Container: Return cylinders to supplier for refill or disposal
- Do not incinerate or puncture

### 14. TRANSPORT INFORMATION

Mode	UN Number	Proper Shipping Name	Class	Packing Group	Hazchem	EMS
Land	UN1013	Carbon Dioxide	2.2	Not applicable	2T	
Sea (IMDG)	UN1013	Carbon Dioxide	2.2	Not applicable	2T	F-C, S-V
Air (IATA)	UN1013	Carbon Dioxide	2.2	Not applicable		_

#### Additional Notes:

- · Classified as a Dangerous Good under NZS 5433, IMDG, and IATA
- Hazard Label:



· Ensure cylinder valves are closed and protected during transport

### **15. REGULATORY INFORMATION**

HSNO Approval Code: HSR001018

**Group Standard:** Compressed Gases (Non-flammable) Group Standard 2017 **Inventory Status:** Listed on NZIoC (New Zealand Inventory of Chemicals)

### **16. OTHER INFORMATION**

- This SDS has been prepared in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017 and GHS 7
- · Ensure safe handling procedures are followed for industrial gas use
- Store in accordance with NZS 5433 and relevant safety requirements
- Revision Date: June 2025